

MAGNUM 2300 BFF

The Magnum 2300 BFF semi automatic case erector allows one operator to quickly form & seal the bottom of up to 15 uniform empty cases per minute. This easy to use system provides an increase in productivity of 3-4 times over labor intensive hand taping, while significantly improving ergonomics to reduce repetitive motion strain.

The low investment cost means the Magnum 2300 BFF also works great as a back-up to a fully automatic case erector and can be used to boost packing line output during peak business seasons.



SYSTEM SPECIFICATIONS

Operating Rate	Up to 15 Cases per Minute
Case Size Capacity	6-24" L, 6-20" W, 3"-Unlimited H, Up to 75 Pounds
Electrical Requirements	120 V, 60Hz, 8 Amp
Pneumatic Requirements	None
Machine Dimensions	71" L x 41" W x 27-35" H Adjustable, 425 Pounds


PREMIUM FEATURES

- Easily adjusts to different case sizes with a turn of the crank handle
- Automatically folds bottom flaps of cases to increase productivity
- Locking swivel casters included for easy maneuvering
- Magnum 200 Series 2" tape head standard, 3" optional
- Included 16" long exit conveyor

MAGNUM 2300 T-Table

The Magnum 2300 T-Table is the most cost effective solution available for one operator to form, pack, close, and seal up to 12 uniform cases per minute. The simple flap folding guides require no additional sensors or complicated moving parts, which makes the system as easy to set up, operate, and maintain as a standard case sealer while providing the productivity of more automated equipment.

Simply place an opened case on the T-Table to form the bottom and slide it forward between the entry guides to hold securely for packing. When the case is full, fold down the top rear flap and push the case into the side belts. The machine folds the remaining top and bottom flaps closed and seals the box automatically.



SYSTEM SPECIFICATIONS

Operating Rate	Up to 12 Cases per Minute
Case Size Capacity	6-24" L, 6-20" W, 5-20" H, Up to 75 Pounds
Electrical Requirements	120 V, 60Hz, 8 Amp
Pneumatic Requirements	None
Machine Dimensions	120" L, 34" W, 23-32" H Adjustable, 410 Pounds

PREMIUM FEATURES

- Easily adjusts to different case sizes with a turn of the crank handles
- T-Table design automatically forms the bottom flaps of the case and holds it down for easy packing
- Locking swivel casters included for easy maneuvering
- Magnum 200 Series 2" tape heads standard, 3" optional
- Included 16" long exit conveyor

MAGNUM 4500 BFF

The Magnum 4500 BFF semi automatic case erector allows one operator to quickly form & seal the bottom of up to 15 empty cases per minute, and will automatically adjust to random case sizes. This easy to use system provides an increase in productivity of 3-4 times over labor intensive hand taping, while significantly improving ergonomics to reduce repetitive motion strain.

The low investment cost means the Magnum 4500 BFF also works great as a back-up to a fully automatic case erector and can be used to boost packing line output during peak business seasons.



SYSTEM SPECIFICATIONS

Operating Rate	Up to 15 Cases per Minute
Case Size Capacity	6-30" L, 6-24" W, 5" - Unlimited H, Up to 75 Pounds
Electrical Requirements	120V, 60 Hz, 10 Amp
Pneumatic Requirements	80 psi, 4 cfm
Machine Dimensions	46" L x 41" W x 30-38" H Adjustable, 675 Pounds

PREMIUM FEATURES

- Automatically folds bottom flaps of cases to increase productivity
- Automatically adjusts to different sized cases
- Magnum 200 Series 2" tape heads standard, 3" optional
- Optional Exit Conveyor
- Locking swivel casters included for easy maneuvering

MAGNUM 4500 T-Table

The Magnum 4500 T-Table is the most cost effective solution available for one operator to form, pack, close, and seal up to 12 cases per minute, and will automatically adjust to random case sizes. The simple flap folding guides require no additional sensors or complicated moving parts, which makes the system as easy to set up, operate, and maintain as a standard case sealer while providing the productivity of more automated equipment.

Simply place an opened case on the T-Table to form the bottom and slide it forward between the entry guides to hold securely for packing. When the case is full, fold down the top rear flap and push the case into the side belts for the machine to take over. The remaining top and bottom flaps are folded closed and sealed automatically.



SYSTEM SPECIFICATIONS

Operating Rate	Up to 15 Cases per Minute
Case Size Capacity	6-30" L, 6-24" W, 5-24" H, 4-75 Pounds
Electrical Requirements	120V, 60 Hz, 10 Amp
Pneumatic Requirements	80psi, 4cfm
Machine Dimensions	46" L x 41" W x 60-72" H Adjustable, 750 Pounds

PREMIUM FEATURES

- T-Table design automatically forms the bottom flaps of the case and holds it down for easy packing
- Automatically adjusts to different sized cases
- Magnum 200 Series 2" tape heads standard, 3" optional
- Optional Exit Conveyor
- Locking swivel casters included for easy maneuvering