

RRC-330 ULTRASONIC COUNTERS

RRC-330 Ultrasonic Label Counters are self-contained, off-line Digital Reel-to-Reel Label Counters that provide a convenient all-in-one solution for accurate and repeatable label counts. These models are made to handle opaque and transparent labels with gaps between them on opaque or transparent liner. The Digital Preset Counter Module on these units can also be programmed to stop automatically when a preset count is reached if desired.



| Technical Specifications | RRC-330-U | RRC-330-AU |
|-----------------------------------|---|-------------------------------------|
| Max Media Width (in) ¹ | 6 (152-mm) | |
| Min Media Width (in) | 0.5 (13-mm) | |
| Max Label Length (in) | N/A | |
| Min Label Length (in) | N/A | |
| Max Roll Weight (lbs) | 17 (8-kg) | |
| Max Roll Diameter (in) | 13 (330-mm) | 12.5 (317-mm) |
| Core Diameter (in) ² | 3 (76-mm) | 3 Unw; 1 - 4 Rwd (76; 25 - 102-mm) |
| Label Type | Opaque <u>and</u> Transparent with Gaps In Between | |
| Liner Type | Opaque <u>and</u> Transparent | |
| Max Speed (ips) | 114 (2895-mm) | 108 (2743-mm) |
| Min Speed (ips) | 0.125 (3-mm) | |
| Max RPM | 168 | |
| Max Torque (in-oz) | 1,837 | |
| Dimensions-HWD (in) | 14.5 x 32.5 x 13 (368 x 825 x 330-mm) | 13 x 32.5 x 13 (330 x 825 x 330-mm) |
| Weight (lbs) | 35 (16-kg) | 36 (16.3-kg) |
| Power Specifications | 120-220VAC in, 24VDC 100W out | |
| Warranty | 3 year limited warranty on Reel-to-Reel Counter - 1 year limited warranty on Counter Display Module & Power Adaptor | |
| Available Options | <ul style="list-style-type: none"> • TSN-RR-6 (Tensioning Kit for pre-2016 models) • RR-1"U (Unwind Shaft for 1" Cores) ³ • RR-1.5"U (Unwind Shaft for 1.5" Cores) ³ • ROLLER KIT, RR-8" (8" Roller Kit) • ROLLER KIT, RR-10" (10" Roller Kit) | |

1. Maximum Media Width can be increased by adding either the 8" (203-mm) or 10" (254-mm) Roller Kit. 09.2016
2. The RRC-330-A is equipped with an Adjustable Core Holder for 1" - 4" (25 - 102-mm) Diameter Cores.
3. This option Modifies the standard 3" (76-mm) diameter Unwind Core Holder to the dimension specified.