

LD-200 SERIES LABEL DISPENSERS

LABELMATE USA Label Dispensers are the highest-quality, easiest to use, most durable and reliable Label Dispensers available. The simple to adjust Reflective Sensor technology utilized by the Dispensers makes it extremely easy to adjust for any label length. As you pick up one label the next one is immediately advanced. The labels are presented at the front of the machine, which is convenient for both left-handed and right-handed operators. Stainless Steel models are available for clean environments.



| Technical Specifications | LD-200-RS | LD-200-U | LD-200-RS-SS | LD-200-U-SS |
|--|--|----------------------|-----------------|----------------------|
| Construction | Powder-Coated Steel | Powder-Coated Steel | Stainless Steel | Stainless Steel |
| Max Label Width (in) | | 6.5 (165-mm) | | |
| Min Label Width (in) | 0.5 (13-mm) | | 0.5 (13-mm) | |
| Max Label Length (in) | N/A | | | |
| Min Label Length (in) | 0.5 (13-mm) | | 0.5 (13-mm) | |
| Label Types | Opaque | Transparent & Opaque | Opaque | Transparent & Opaque |
| Max Roll Diameter (in) | 8.6 (220-mm) | | | |
| Core Diameter (in) | 1.5 or Larger (38-mm) | | | |
| Max Speed (ips) | 8 (203-mm) | | | |
| Dimensions-HWD (in) | 10.5 x 10 x 8 (267 x 254 x 203-mm) | | | |
| Weight (lbs) | 15 (6.8-kg) | | 16 (7.3-kg) | |
| Power Specifications ¹ | 120VAC in, 12VAC 40W Out | | | |
| Warranty | 3 Year Limited Warranty on Label Dispenser; 1 Year Limited Warranty on Power Adaptor | | | |
| Available Options | <ul style="list-style-type: none"> • LDC-1 (Digital Label Counter) ² • BP-LD (Mobile Battery Pack & Charger) • TSN, LD-6 (Web-Tensioning Shaft) ³ • FLANGES-LD (Supply Roll Flange Plates) • LD-ES (External Start Feature) | | | |

1. 220VAC input available at the time of order.

2. Not available on -SS Stainless Steel Models.

3. Available for 3" diameter (76-mm) cores only.